

MAGNUM OIL TOOLS INTERNATIONAL

 Print Page
  Pdf Page
  Add To Report
  Report Center


Dual MagnumDisk Box x Wireline Re-Entry W/Mule Shoe

Description:

This is a patented, field proven, frangible, debris-free, knockout plug that is run on the bottom of the tubing, plug, or packer. After the packer is set, the wellbore is then isolated below the packer. When the tubing is landed, and all jewelry and assembly is in place, a bar can be dropped, coil tubing, slickline, or sandline can be used to rupture the ceramic disk. This will allow wellbore fluids to flow up the tubing or a frac to flow up the tubing, with no debris to interfere with your lower assemblies.

Features:

- Economical alternative to profile nipple with a plug
- No plug pulling problems
- Maximum surge potential of formation after perforating
- Option of using a slick line, drop bar, coil tubing, or sand line to rupture
- The Dual Magnumdisk™ allows for tubing testing up to 10,000 psi.
- Can be ran in mud environment
- No interfering debris left in the wellbore
- Full opening after rupturing
- Can be run in 450° temperature wells
- The Dual Magnumdisk™ may be pressure tested previous to installation
- Reusable, with redressing kit and simple assembly procedure
- All Magnumdisk™ can be manufactured with premium threads



Specifications: (Inches & Fahrenheit)

PART #	DESCRIPTION	INTERNAL DIAMETER	EXTERNAL DIAMETER	BOTTOMSIDE DISK RATING	TOPSIDE DISK RATING
01.MDDA.100.CSBM	1.0" CS HYDRIL DUAL MAGNUMDISK™	.957	1.901	8,000 PSI	8,000 PSI
01.MDDA.114.1NBM	1 1/4" NU 10RD DUAL MAGNUMDISK™	1.380	2.125	10,000 PSI	10,000 PSI
01.MDDA.216.IJBM	2 1/16" IJ DUAL MAGNUMDISK™	1.610	2.500	10,000 PSI	10,000 PSI
01.MDDA.238.8EBM	2 3/8" EU 8RD DUAL MAGNUMDISK™	1.995	3.060	10,000 PSI	10,000 PSI
01.MDDA.278.8EBM	2 7/8" EU 8RD DUAL MAGNUMDISK™	2.441	3.670	10,000 PSI	10,000 PSI
01.MDDA.312.8EBM	3 1/2" EU 8RD DUAL MAGNUMDISK™	2.992	4.500	10,000 PSI	10,000 PSI
01.MDDA.41L.LTBM	4 1/2" LT&C 8RD DUAL MAGNUMDISK™	3.958	5.625	10,000 PSI	10,000 PSI
01.MDDA.51L.LTBM	5 1/2" LT&C 8RD DUAL MAGNUMDISK™	5.00	6.625	10,000 PSI	10,000 PSI
01.MDDA.700.LTBM	7.00" LT&C 8RD DUAL MAGNUMDISK™	6.366	8.250	10,000 PSI	10,000 PSI