

MAGNUM

OIL TOOLS

INTERNATIONAL

[Print Page](#)
[Pdf Page](#)
[Add To Report](#)
[Report Center](#)

Magnum Mill-EZ Flo-Back Composite Bridge Plug

Description:

The "MAGNUM MILL-EZ™ FLO-BACK" is a patented slim design Composite Bridge Plug, with a built in one way check valve. This tool is set like a conventional bridge plug. When the pressure below the plug is greater than the pressure above, the check valve will allow the two zones to commingle. The operator can independently treat or test each zone and then remove the flo-back plug or plugs in one trip. Because of its low metallic content the "MAGNUM MILL-EZ™ FLO-BACK" can be quickly and easily milled and circulated back to surface. This may be accomplished with conventional milling or drilling with a rig and tubing or with coiled tubing.



Features:

- Can be set on wireline, coiled tubing, or production tubing
- Utilizes conventional setting tools
- Multiple plugs in a single well bore
- Mill or drill multiple plugs in a single run
- Can be milled or drilled with coil tubing
- Utilize conventional milling or drilling tools
- High differential pressure rating
- Positive ball seat check valve system
- Custom Plug O.D. available upon request

Specifications: (Inches & Fahrenheit)

PART NUMBER ("X" DENOTES PRESSURE AND TEMP OF PLUG G, Y, OR B)	CASING O.D.	WEIGHT	Bridge Plug O.D	Bridge Plug Length	LOW Temp. & LOW PSI. GREY	LOW Temp. & HIGH PSI. YELLOW	HIGH Temp. & HIGH PSI. BLUE	Recommended Setting Tool
05.CFBA.278.220X	2 7/8"	6.5	2.20	11.0		250° / 10K	400° / 10K	Baker #5 or GO
05.CFBA.278.215X	2 7/8"HW	7.9	2.15	11.0		250° / 10K	400° / 10K	Baker #5 or GO
05.CFBA.312.273X	3 1/2"	9.30-10.20	2.725	11.0		250° / 10K	400° / 10K	Baker #5 or GO
05.CFBA.31H.250X	3 1/2"HW	12.95	2.50	11.0		250° / 10K	400° / 10K	Baker #5 or GO
05.CFBA.400.325X	4"	9.50-11.00	3.188	16.0	250° / 8K	250° / 10K	400° / 10K	Baker #10 or GO
05.CFBA.412.360X	4 1/2"	9.50-15.10	3.60	16.0	250° / 8K	250° / 10K	400° / 10K	Baker #10 or GO
05.CFBA.500.400X	5"	11.50-20.00	3.92	16.0	250° / 8K	250° / 10K	400° / 10K	Baker #10 or GO
05.CFBA.512.440X	5 1/2"	15.50-23.00	4.40	16.0	250° / 8K	250° / 10K	400° / 10K	Baker #20 or GO
05.CFBA.700.575X	7"	20.00-35.00	5.75	18.0	250° / 8K	250° / 10K	400° / 10K	Baker #20 or GO
05.CFBA.758.640B	7 5/8"	24.00-33.70	6.40	18.0			400° / 10K	Baker #20 or GO
05.CFBA.858.713Y	8 5/8"	36.00-49.00	7.25	22.0		250° / 8K		Baker #20 or GO
05.CBPA.958.825Y	9 5/8"	32.30-53.50	8.375	22.0		250° / 8K		Baker #20 or GO